

Package: pearson7 (via r-universe)

October 9, 2024

Version 1.0-3

Date 2020-05-07

Title Maximum Likelihood Inference for the Pearson VII Distribution
with Shape Parameter $3/2$

Author John Hughes

Maintainer John Hughes <drjphughesjr@gmail.com>

Description Supports maximum likelihood inference for the Pearson VII
distribution with shape parameter $3/2$ and free location and
scale parameters. This distribution is relevant when estimating
the velocity of processive motor proteins with random
detachment.

License GPL (≥ 2)

Collate 'pearson7.R' 'zzz.R'

RoxygenNote 5.0.1

NeedsCompilation no

Date/Publication 2020-05-08 09:30:03 UTC

Repository <https://drjphughesjr.r-universe.dev>

RemoteUrl <https://github.com/cran/pearson7>

RemoteRef HEAD

RemoteSha 348a97c4b4ad5fe525dc0f3c099e96bfc8486b97

Contents

| | |
|------------------------------|---|
| dpearson7 | 2 |
| pearson7.fit | 3 |
| pearson7.objective | 4 |
| ppearson7 | 5 |
| qpearson7 | 6 |
| rpearson7 | 7 |
| summary.pearson7 | 8 |

| | |
|--------------|----------|
| Index | 9 |
|--------------|----------|

| | |
|-----------|--|
| dpearson7 | <i>Evaluate the density for the Pearson VII distribution with shape parameter 3/2.</i> |
|-----------|--|

Description

Evaluate the density for the Pearson VII distribution with shape parameter 3/2.

Usage

```
dpearson7(x, mu = 0, sigma = 1, log = FALSE)
```

Arguments

| | |
|-------|--|
| x | vector of quantiles. |
| mu | vector of means. |
| sigma | vector of scales. |
| log | logical; if TRUE, probabilities p are given as log(p). |

Details

If mu is not specified, it assumes the default value of 0. If sigma is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has density

$$f(x) = 1/(2\sigma)[1 + \{(x - \mu)/\sigma\}^2]^{-3/2}.$$

Value

the density.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

Pearson, K. (1916) Mathematical contributions to the theory of evolution. xix. second supplement to a memoir on skew variation. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, **216**, 429–457.

See Also

[ppearson7](#), [qpearson7](#), [rpearson7](#)

Examples

```
curve(dpearson7(x), -5, 5, lwd = 2, n = 500, ylab = "f(x)")
curve(dnorm(x), lwd = 2, lty = 2, n = 500, add = TRUE)
```

| | |
|--------------|--|
| pearson7.fit | <i>Find the MLE for a sample from the Pearson VII distribution with shape parameter 3/2.</i> |
|--------------|--|

Description

Find the MLE for a sample from the Pearson VII distribution with shape parameter 3/2.

Usage

```
pearson7.fit(y, mu0 = median(y), sigma0 = sqrt(3) * median(abs(y -  
median(y))), tol = 1e-08)
```

Arguments

| | |
|--------|---------------------------------|
| y | a vector of observations. |
| mu0 | an initial value for μ . |
| sigma0 | an initial value for σ . |
| tol | the convergence tolerance. |

Details

This function uses a Newton-Raphson algorithm to find the MLE. The starting values for μ and σ are the sample median and $\sqrt{3}$ times the sample MAD, respectively. See the reference for details.

Value

pearson7.fit returns an object of class "pearson7", which is a list containing the following components.

| | |
|------------|--|
| theta.hat | the estimates of μ and σ . |
| hessian | the Hessian matrix evaluated at theta.hat. |
| iterations | the number of iterations required to attain convergence. |
| value | the value of the log likelihood at theta.hat. |

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also

[pearson7.objective](#)

Examples

```
y = rpearson7(100, 100, 10)
fit = pearson7.fit(y)
fit
summary(fit)
```

pearson7.objective *Compute the negative log likelihood for a sample.*

Description

Compute the negative log likelihood for a sample.

Usage

```
pearson7.objective(params, y)
```

Arguments

params a vector of parameter values.
y a vector of observations.

Details

This function computes the negative log likelihood for (μ, σ) given a sample. This function can be optimized using [optim](#), but it is better to use [pearson7.fit](#).

Value

the negative log likelihood.

See Also

[dpearson7](#), [pearson7.fit](#)

ppearson7 *Evaluate the distribution function for the Pearson VII distribution with shape parameter 3/2.*

Description

Evaluate the distribution function for the Pearson VII distribution with shape parameter 3/2.

Usage

```
ppearson7(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
```

Arguments

| | |
|------------|--|
| q | vector of quantiles. |
| mu | vector of means. |
| sigma | vector of scales. |
| lower.tail | logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise $P(X > x)$. |
| log.p | logical; if TRUE, probabilities p are given as log(p). |

Details

If mu is not specified, it assumes the default value of 0. If sigma is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has cdf

$$F(x) = \{1 + (x - \mu) / \sqrt{\sigma^2 + (x - \mu)^2}\} / 2.$$

Value

the probability.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also

[dpearson7](#), [qpearson7](#), [rpearson7](#)

Examples

```
curve(ppearson7(x), 0, 5, lwd = 2, ylim = c(0.8, 1), ylab = "F(x)")
curve(pnorm(x), lwd = 2, lty = 2, add = TRUE)
```

`qpearson7` Evaluate the quantile function for the Pearson VII distribution with shape parameter 3/2.

Description

Evaluate the quantile function for the Pearson VII distribution with shape parameter 3/2.

Usage

```
qpearson7(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
```

Arguments

| | |
|-------------------------|--|
| <code>p</code> | vector of probabilities. |
| <code>mu</code> | vector of means. |
| <code>sigma</code> | vector of scales. |
| <code>lower.tail</code> | logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise $P(X > x)$. |
| <code>log.p</code> | logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$. |

Details

If `mu` is not specified, it assumes the default value of 0. If `sigma` is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has quantile function

$$F^{-1}(x) = \mu + (\sigma/2)(2x - 1)/\sqrt{x(1-x)}.$$

Value

the quantile.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also

[dpearson7](#), [ppearson7](#), [rpearson7](#)

Examples

```
curve(qpearson7(x), 0, 1, lwd = 2, ylab = expression(F^{-1}(x)))
curve(qnorm(x), lwd = 2, lty = 2, n = 500, add = TRUE)
```

| | |
|-----------|---|
| rpearson7 | <i>Generate random deviates from a Pearson VII distribution with shape parameter 3/2.</i> |
|-----------|---|

Description

Generate random deviates from a Pearson VII distribution with shape parameter 3/2.

Usage

```
rpearson7(n, mu = 0, sigma = 1)
```

Arguments

| | |
|-------|-------------------------|
| n | number of observations. |
| mu | vector of means. |
| sigma | vector of scales. |

Details

If mu is not specified, it assumes the default value of 0. If sigma is not specified, it assumes the default value of 1.

Value

random deviates.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

Devroye, L. (1986) *Non-Uniform Random Variate Generation*. New York: Springer-Verlag.

See Also

[dpearson7](#), [ppearson7](#), [qpearson7](#)

Examples

```
y = rpearson7(1000)
hist(y, prob = TRUE, breaks = 100, col = "gray")
curve(dpearson7(x), lwd = 2, col = "blue", add = TRUE)
```

summary.pearson7 *Print a summary of a Pearson VII fit.*

Description

Print a summary of a Pearson VII fit.

Usage

```
## S3 method for class 'pearson7'  
summary(object, alpha = 0.05, digits = 4, ...)
```

Arguments

| | |
|--------|---|
| object | an object of class “pearson7”, the result of a call to pearson7.fit . |
| alpha | the significance level used to compute the confidence intervals. The default is 0.05. |
| digits | the number of significant digits to display. The default is 4. |
| ... | additional arguments. |

Details

This function displays (1) a table of estimates, (2) the value of the log likelihood, and (3) the number of Newton-Raphson iterations. Each row of the table of estimates shows the parameter estimate and the approximate $(1 - \alpha)100\%$ confidence interval for the parameter.

See Also

[pearson7.fit](#)

Index

dpearson7, 2, 4-7

optim, 4

pearson7.fit, 3, 4, 8

pearson7.objective, 3, 4

ppearson7, 2, 5, 6, 7

qpearson7, 2, 5, 6, 7

rpearson7, 2, 5, 6, 7

summary.pearson7, 8